

EST3607CAN Fieldbus Pressure Transmitter

- ✓ Pressure type: Gauge/Seal Gauge Pressure
- ✓ CAN Fieldbus output
- ✓ Range: 0~0.07...1000 bar
- ✓ Accuracy: $\pm 0.25\%F.S/0.5\%/FS$
- ✓ Operating temperature: $-40^{\circ}C \sim 85^{\circ}C$
- ✓ Communication distance: 10Km
- ✓ OEM: Available



Applications

Hydrologic monitoring | Constant pressure water supply | Tailwater elevation | Wastewater treatment | Frequency water supply

Product Introduction

EST3607 line features high reliability, stability, and accuracy. The product is widely used for the measurements of gas and liquid, such as water and oil. With a built-in CAN fieldbus controller and transceiver, EST3607 enables CANBUS-based two-way communication. The longest communication distance is up to 10km, and the communication rate is up to 1Mbps.

Highlight features

- CAN 2.0 bus supports the DS301 version of the CANopen protocol.
- Process connection of G1/4, 7/16-20UNF-2B (F), 7/16-20UNF-2A (M), NPT1/4, G1/2
- Data transmission rate up to 125 Kbps with high real-time performance.
- Transmission distance up to 10 km, capable of operating in high noise interference environments.
- Features priority and arbitration functions, allowing for multiple control modules to be mounted and form a multi-master local network.
- Reliable error handling with strong error detection capabilities; can automatically retransmit information when corrupted; automatically exits the bus during severe errors.

Electrical /Process Connections

Electrical connection								
DIN43650-C			M12X4P			Cable outlet		
Wire	CAN		Wires	CAN		Wires	CAN	
1	Power (U+)		1	Power (U+)		Red	Power (U+)	
2	GND		2	CANH		Black	GND	
3	CANH		3	GND		Green	CANH	
≡	CANL		4	CANL	White	CANL		
Packard		M12X4P	Cable outlet		DIN43650-C	GX12-		

General Instruction and Datasheet

EST3607 GID-3-EV03.3

Measuring your business

C1		C2		C3		C4		C5		
Current	Voltage	Current	Voltage	I2C	Current	Voltage	Current	Voltage	Current	Voltage
2-wire	3-wire	2-wire	3-wire	4-	2-wire	3-wire	2-wire	3-wire	2-wire	3-wire
Process connection										
G1/4		7/16-20UNF-2B		7/16-20UNF-2A		NPT1/4		G1/2		

General Instruction and Datasheet

EST3607 GID-3-EV03.3

Measuring your business

Specifications

Range	0...0.07~0...1000 bar; Gauge/Sealed		Response Time	(10%~90%)≤10ms
Output	CAN 2.0/; CANOPEN Protocol / DS301v		Over-pressure	≥150%F.S
Power Supply	(5±0.25) VDC	10VDC~30VDC	Burst-pressure	≥200%F.S, 1000 bar (max)
Working Current	≤30mA	≤30mA	Process Connection	G1/4, 7/16-20UNF-2B-
Voltage	12VDC	30VDC	Electrical Connection	DIN43650-C,M12 ×1, Water-
Inverse Voltage	12VDC	-30VDC	O-Ring for wetted part	NBR; FKM
Accuracy @25C	±0.5%F.S (default), ±0.25%(optional)		MOC/Housing	SS304; SS316L
Temp. Compensation	0°C~50°C		Insulation Resistance	≥100MΩ @100VDC
Working Temp.	-30°C~80°C, -10°C~70°C(Cable)		Vibration	10g, 5~2000Hz
Medium Temp.	-30~120°C		Shock	20g, 11ms Half sine
Storage Temp.	-40°C~85°C, -20°C~85°C(Cable)		Ingress Protection	≥IP65
Long-term Stability	±0.25%FS/Y			

1MPa=10bar; 1bar≈14.5PSI; 1PSI=6.8965kPa; 1kgf/cm2=1atm; 1atm≈98kPa

Ordering Procedure

EST	Pressure transducer for air compressor industry									
	Code	Model								
	3607	A/B/C								
		Cod	Span							
		X	0~X bar							
			Code	Output Type						
			CAN	CAN						
				Code	Precision					
				05	±0.5%F.S					
				02	±0.25%F.S					
					Code	Power Supply				
					DC10	10~30 Vdc				
					DC5	(5±0.25) VDC				
						Code	Pressure connections			
						G	G1/4			
						N	NPT1/4			
						U	7/16-20UNF -22B			
						M	M20x1.5			
						G2	G1/2			
							Code	Electrical Connections		
							H	DIN43650C		
							GX	GX12-3		
							C	Wire jacket protection		
							CW	Waterproof cable conduit connections		
							P	Packard		
								Code	Cable length XXm=... m	
									Code	Packing
									Bb	Bubble bag
									Foa	Plastics foam

EST 3607 100bar CAN 05 DC10 G H 1.5m Bb

Note:

1: For products with a range less than 0.2 bar or greater than 20 MPa, please consult the manufacturer for tailor-made solution.
 2: The medium temperature mainly depends on the sealing material. The default NBR sealing ring allows for a medium temperature of -30 to 120°C. If you choose the FKM sealing ring, the medium temperature can be -20 to 125°C. If the medium temperature exceeds 85°C for long periods, please specify this explicitly.